

TANNERS CHOICE PROTECTOR

Leather Protector and Restorer

Product

- ✓ Ensures leather does not dry out or crack prematurely
- ✓ Forms a film that penetrates and bonds to the surface, creating a tough barrier layer that helps resist spillages, abrasives and grime
- ✓ Contains no silicone based products that offer poor protection against hot or oil based spills
- ✓ Once protected leather sheds dust making it easier to clean



Leather cleaner and protection that is simple and safe on all leathers. When applied to freshly cleaned or new leather it dries to a natural soft sheen and will only show higher sheen when more than two coats are applied.

Technical

Colour	White
Odour	Ketone
pH	N/A
Dangerous Goods Classification	
ADG CODE	1263, PAINT
HAZCHEM	•3Y
CLASS	3: Flammable liquids
PACK GRP	III



Product Code	Outer Pack	APN
CHRC-20606 (1L)	6	9324828002451

Application

Method

1. Do not dilute. Use neat. Apply using a clean, damp and lint free cloth.
2. Pour a small quantity of PROTECTOR onto a pad and apply to back of the article first in firm even strokes, slightly rubbing into edges and crevices. Never rub freshly applied coats as this will permanently smear or streak the partly dried surface.
3. If the coat is uneven, buff out with dry towelling after the surface is tack free after about 10 mins.
4. A second coat can be applied across the direction of the previous coat to increase protection on seat, cushions and arm rests. (This may be required on seat cushions and arm rests where heavy wear protection is required).
5. Allow approximately 30 – 45 minutes to dry between coats.
6. Repeat process section by section until item has been coated.
7. After surface has been protected it will be safe to use once the solvent smell has dissipated (usually a few hours after treatment).

Continued next page

TANNERS CHOICE PROTECTOR

Leather Protector and Restorer

Application precautions:

- ✓ DO NOT apply in direct sun light or areas of strong wind, as high speed drying increases the chance for streaking and poor levelling.
- ✓ Dampen clean non-linting flannel or pure cotton cloth (not towelling) if weather is hot. DO NOT add water to Protector as this will promote streaking. Once you are experienced, a dry flannel may be used.
- ✓ Wring out all excess water and double over to make a pad.
- ✓ This system is NOT suitable for or on Nubuck or suede surfaces.

Hazard Statement

- H226: Flammable liquid and vapour.
- H315: Causes skin irritation.
- H320: Causes eye irritation.
- H335: May cause respiratory irritation.
- AUH066: Repeated exposure may cause skin dryness or cracking.

Prevention

- P102: Keep out of reach of children.
- P210: Keep away from heat, sparks, open flames and hot surfaces. - No smoking.
- P243: Take precautionary measures against static discharge.
- P261: Avoid breathing fumes, mists, vapours or spray.
- P264: Wash contacted areas thoroughly after handling.
- P271: Use only outdoors or in a well ventilated area.
- P280: Wear protective gloves, protective clothing and eye or face protection.