



TASKI®

Vectra



F2

Sealer/Finish

Description

TASKI® Vectra is a high performance fast curing floor finish for use on all internal resilient floors such as vinyl and porous composite tiles. TASKI® Vectra delivers diamond like brilliance and clarity across a wide variety of surfaces. TASKI® Vectra can be top coated over any Diversey sealer for even more flexible floorcare solutions.

Features

- Can be used as a scrub and recoat finish.
- Resists scuffing, dirt and marking.
- TASKI® Vectra gives high levels of gloss, durability and good levelling.
- Suitable for most types of floors.
- Easy to maintain.
- Diamond like brilliance and clarity.

Benefits

- TASKI® Vectra is fast curing and extremely hard, with excellent adhesion and scuff resistance which reduces the need for recoats, saving time and labour.
- Resists black heel marks and scuffs.
- Responds well to spray buffing which means floor will retain its gloss for longer between recoats.
- Excellent gloss and clarity ensuring long term floor appearance.

Application areas

- Retail
- Education
- Government
- Healthcare
- Institutional Facilities





TASKI®

Vectra



F2

Sealer/Finish

Directions for use

Application:

1. Strip old coatings using a Diversey stripper according to label directions.
2. Apply 2-3 coats using a clean mop. If higher gloss is desired apply additional coats.
3. Allow 30 minutes drying time between coats.

Maintenance:

1. Dust, mop or sweep.
2. Clean floor using recommended Diversey brands cleaner according to label directions.
3. If desired, spray buff or high speed spray buff using recommended Diversey brand floor maintainer to enhance gloss.

Before recoating:

1. Dust mop or sweep.
2. Deep scrub floor using recommended Diversey brand cleaner according to label directions.
3. Apply 1-2 coats using a clean mop.

For best results:

- Do not dilute.
- Do not use on surfaces colder than 10°C.
- To avoid contamination, do not return unused product to original container.
- Not intended for use in outdoor areas.

Technical data

Appearance	Opaque off white liquid	Odour	Product specific
pH (concentrate)	8.6	Specific gravity (20°C)	1.03
Coverage	50 – 60m ² per litre	Slip classification	D1 (AS 4586:2013)
Maintenance speed	175 – 1500 rpm	Dilution	Neat

The above data is typical of normal production and should not be taken as a specification.

Product	Pack size	SKU Code	Availability
TASKI® Vectra	2 x 5L	5687631	AU & NZ

Safe handling and storage information

Full guidance on the handling and disposal of this product is provided in a separate Safety Data Sheet. Store in original container. Avoid extremes of temperature and humidity.

Product compatibility

Under recommended conditions of use, TASKI® Vectra is suitable for use on most floor types. Non-resilient (porous) floors must be sealed first before applying finish. Ideal for low maintenance, spray buffing program.

Safety Reminder

Please make sure your employees read and understand the product label and Safety Data Sheet before using this product. The label contains directions for use, and both the label and SDS contain hazard warnings, precautionary statements and first aid procedures. SDSs are available online at www.diversey.com or by calling Toll free: Australia, 1800 647 779 or New Zealand, 0800 803 615.

For additional information, please contact us at:

Diversey Australia Pty Ltd Toll free: 1800 647 779, Diversey New Zealand Ltd Toll free: 0800 803 615 www.diversey.com.

Legal disclaimer: The associated products or services are manufactured by or otherwise emanate from Diversey Companies and their subsidiaries and not from Sealed Air.