

Product Information Sheet



GLAZER

Floor Sealer Finish



Product

- ✓ Easy to lay and maintain
- ✓ Suitable for use with both regular speed and UHS equipment
- ✓ Excellent scuff, black heel mark and wear resistance
- ✓ Perfect for floors that are repeatedly buffed
- ✓ Maintains its shine even under extreme traffic conditions
- ✓ Extremely versatile and suitable where low maintenance is required



Glazer is perfect for use in all heavy traffic areas such as shopping malls, railway stations, hospitals, nursing homes and office buildings. Ideal sealer-finish for vinyl floors for mop and re-coat applications and also ideal as a sacrificial coating for timber floors coated with urethane based coatings. It is suitable for all resilient floors including vinyl tiles, vinyl asbestos tiles, rubber, composite rubber and linoleum. Also suitable for most hard floors like marble, slate and terrazzo. However, some hard glazed quarry tiles and glazed ceramic tiles are unsuited to using GLAZER due to the lack of porosity.

Technical

Colour	Milky White
Odour	Polymer Odour
pH	8.00 – 9.00
Solids (%)	22.00
Coverage (m ² /Lit)	50 – 60
Gloss (% @ 60°)	70 - 80

Product Code		Outer Pack	APN
CHRC-602006	(1L)	6	9324828001133
CHRC-6020015A	(5L)	3	9324828001140
CHRC-602015	(15L)	1	9324828001157

Application

Refer to task sheet – “How to Seal Floors” for correct application procedure.

Task	Method
Floor Preparation	<ol style="list-style-type: none">1. Strip off old seals or finished with STEAMROLLER II, MELTDOWN or SLEDGEHAMMER as directed. SLEDGEHAMMER is highly effective in removing GLAZER, however in areas where a base coat (BEDROCK or BLOCKADE) have been used, strip the floor using STEAMROLLER II.2. If stripping is not required, cut back the floor with SUPASTAR as directed using Oates Floormaster Blue scrubbing pad.
Finish Application	<ol style="list-style-type: none">1. BEDROCK may be used as a pre-sealer if the floor is highly porous.2. Apply three to four coats of GLAZER using an Oates Poly-Cotton mop or Nylon Polish Spreader (SM-156).3. Allow 30-45 mins between coats or until it is completely dry.
Maintenance	<ol style="list-style-type: none">1. A good floor maintenance program will extend the life of your floor finish and extend the time between stripping and resealing.2. Dust mop daily to remove sand and grit tracked over the floor, and where possible use

Version: 1 Page 1 of 1

Research Products recommends you obtain and read the Safety Data Sheet (SDS) before using any product, available from www.oateslaboratories.com.au. This Product Information Sheet is offered without guarantee as the conditions and method of application of this product are beyond our control.



E.D. Oates Pty Ltd ABN 61 004 329 462
13-21 Maygar Boulevard, Broadmeadows VIC 3047
Customer Service: 1300 669 686 | Website: www.oateslaboratories.com.au

Oates is a division of GUD Holdings Ltd (ABN 99 004 400 891)

Product Information Sheet



GLAZER

Floor Sealer Finish



	carpet matting in entrance ways. 3. Mop or auto scrub daily using SUPASTAR as directed. Dry burnish or spray buff using SHINER.
--	--

Hazard Statement

H316: Causes mild skin irritation.

Prevention

P102: Keep out of reach of children.

P264: Wash affected areas thoroughly after handling.

P280: Wear protective gloves, protective clothing and eye or face protection.