

SPARTACUS

Sealer Finish



Product

- ✓ A top performer with increased toughness and flexibility
- ✓ Can be burnished with regular to ultra-high speed machinery
- ✓ Excellent scuff, black heel mark and dirt pick up resistance
- ✓ Provides a brilliant rich, deep, clear wet-look gloss that is extremely resistant to scratches and marks



Easy to lay and maintain sealer polish provides excellent gloss and easy burnishing. Ideal finish for various floor types including terrazzo and stone. Offers a great combination of gloss, wear resistance and performance.

Technical

Colour	Milky White
Odour	Polymer odour
pH	8.00 – 9.00
Solids (%)	19.00
Coverage (m ² /Lit)	50 – 60 (Typical)
Gloss (% @ 60°)	50 – 60

Product Code	Outer Pack	APN
CHRC-630015A (5L)	3	9324828002260
CHRC-630015 (15L)	1	9324828002277

Application

Refer to task sheet – “How to Seal Floors” for correct application procedure.

Task	Method
Preparation	<ol style="list-style-type: none"> 1. Strip off old seals or finishes with STEAMROLLER II or SLEDGEHAMMER as directed. In areas where a base coat (BEDROCK or BLOCKADE) have been used, strip the floor using STEAMROLLER II. 2. If stripping is not required, cut back the floor with SUPASTAR as directed using Oates Floormaster Blue scrubbing pad.
Finish Application	<p>Terrazzo and porous stone: always pre-seal with BLOCKADE or BEDROCK. Vinyl floors: If required, pre-seal the floor with BEDROCK.</p> <ol style="list-style-type: none"> 1. Apply three to four coats of SPARTACUS using an Oates Poly-cotton mop or Nylon Polish Spreader. 2. Allow at least 30-45 minutes between coats or until floor is completely dry.
Maintenance	<ol style="list-style-type: none"> 1. A good floor maintenance program will extend the life of your floor finish and extend the time between stripping and resealing. 2. Dust mop daily to remove sand and grit tracked over the floor, and where possible use carpet matting in entrance ways. 3. Mop or auto scrub daily using SUPASTAR as directed. Dry burnish or spray buff using SHINER. Recommended pads: Buffing low speed: Oates Floormaster Tan buffing pad Buffing high speed: Oates Floormaster Pro-Burnish Lite pad

Product Information Sheet



SPARTACUS

Sealer Finish



Hazard Statement

H316: Causes mild skin irritation.

Prevention

P102: Keep out of reach of children.

P264: Wash affected areas thoroughly after handling.

P280: Wear protective gloves, protective clothing and eye or face protection.

Version: 2 Page 2 of 1

Research Products recommends you obtain and read the Safety Data Sheet (SDS) before using any product, available from www.oateslaboratories.com.au.

This Product Information Sheet is offered without guarantee as the conditions and method of application of this product are beyond our control.



E.D. Oates Pty Ltd ABN 61 004 329 462

13-21 Maygar Boulevard, Broadmeadows VIC 3047

Customer Service: 1300 669 686 | Website: www.oateslaboratories.com.au

Oates is a division of GUD Holdings Ltd (ABN 99 004 400 891)