Colourless

| Floor Stripping | ethod | | |
|--------------------------|--|-------------|--|
| Dilution rate: | 1. Prepare the correct dilution according to finish build up. | | |
| | Generously spread the floor stripping solution over area with mop and bucke | et. | |
| Heavy build-up: | Allow the solution to work and break down existing polish films (generally be | tween 5 to | |
| 1 to 2 parts warm water | 10 minutes). Do not allow the stripping solution to dry. | | |
| | Use an Oates Floormaster Black heavy duty stripping pad to scrub the floor. | | |
| Medium build-up: | Scrub length wise along skirting boards. Then strip side to side over the rema | ining area. | |
| 1 to 5 parts warm water | Use the hand scrub pad to detail strip along the edges and in the corners of the Heel the floor machine on badly soiled spots. Avoid splashing stripper on wal | | |
| Machine scrubbing: | Work in a controlled area to avoid walking on the wet area. | | |
| 1 to 12 parts warm water | Use a wet pick-up vacuum to remove stripper solution from the floor. | | |
| | Do not allow the dirty solution to dry on the floor. | | |
| |). Use a clean mop and clean water. Cover area liberally with rinse water. | | |
| | Pick up the rinse water with the wet pick-up vacuum. Wipe all skirting boards they dry. | s before | |
| | Damp mop the floor with clear water for the final rinse and to ensure that all solution has been removed. | stripper | |

Product Information Sheet

MELTDOWN

Floor Finish Stripper

Product

- Removes most difficult floor finishes in quick time
- High solvent floor stripper
- \checkmark **Contains Ammonia**

High solvent stripper for fast penetration and removal of heavy build up and floor finishes. Suitable for use on non-metallic floor finishes and sealers including polyurethane fortified acrylics.

Technical

| Colour | Colourless | Product Code | | Outer Pack | APN |
|--------|---------------|--------------|----------|------------|---------------|
| Odour | Sweet fruity | CHRC-73015A | (5L) | 3 | 9324828000464 |
| рН | 12.50 - 13.50 | CHRC-73015 | (15L) | 3 | 9324828000471 |
| | | | <u> </u> | | |
| A | | | | | |

Hazard Statement

H314: Causes skin severe skin burns and eye damage.

H320: Causes severe eye damage.

H335: May cause respiratory irritation.

Version: 2 Page 1 of 1

Research Products recommends you obtain and read the Safety Data Sheet (SDS) before using any product, available from www.oateslaboratories.com.au. This Product Information Sheet is offered without guarantee as the conditions and method of application of this product are beyond our control.







Product Information Sheet




MELTDOWN

Floor Finish Stripper

PREVENTION

- P102: Keep out of reach of children.
- P264: Wash contacted areas thoroughly after handling.
- P280: Wear protective gloves, protective clothing and eye or face protection.



Research Products recommends you obtain and read the Safety Data Sheet (SDS) before using any product, available from www.oateslaboratories.com.au. This Product Information Sheet is offered without guarantee as the conditions and method of application of this product are beyond our control.



E.D. Oates Pty Ltd ABN 61 004 329 462 13-21 Maygar Boulevard, Broadmeadows VIC 3047 Customer Service: 1300 669 686 | Website: <u>www.oateslaboratories.com.au</u>

