



CREATING A CLEANER, SAFER, HEALTHIER WORLD.



R14

DUAL-TECHNOLOGY CARPET CLEANER

- Create beautiful carpets in minutes with ReadySpace® technology
- Remove the most deeply embedded dirt with superior restorative extraction technology
- Help inhibit mold and bacteria growth by leaving up to 90% less water in the carpet immediately after cleaning

OUTSTANDING DUAL-TECHNOLOGY CARPET CLEANING FROM A SINGLE MACHINE



The R14 combines patented ReadySpace® technology with deep extraction power to deliver unbeatable carpet cleaning results.

CREATE FRESHER, HEALTHIER ENVIRONMENTS

Using 80% less water to clean, and leaving up to 90% less water in the carpet, the R14 with ReadySpace helps reduce mold and bacteria growth and leaves spaces cleaner and healthier.

INCREASE ENVIRONMENTAL SAFETY

Since carpets dry faster with ReadySpace technology, the risk of slip-and-fall accidents when transitioning from just-cleaned carpet to hard floor is noticeably reduced.

EFFECTIVELY CLEAN THE LARGEST CARPETED SPACES

With a wide 28 in / 710 mm cleaning path, a generous 32 gal / 121 L Hygenic* solution tank, and three hour battery run time, the R14 with ReadySpace delivers continuous cleaning time.

POWERFUL RESTORATIVE EXTRACTION TECHNOLOGY

Tennant pioneered extraction technology and with the R14, we deliver the most effective deep extraction available. Dual counter-rotating extraction brushes combine with patented vacuum shoe design to leave carpets fresh, clean, and looking like new.

INSIDE THE

R14



patented vacuum shoe design that features maximum water suction across the entire cleaning path.



CARPETS CLEAN, DRY AND READY IN MINUTES

Patented ReadySpace* technology creates clean carpet spaces that are dry and ready to use in less than 30 minutes.

Consider the benefits:

- Reopen rooms and carpeted areas sooner
- Keep space accessible to guests and customers
- Improve carpet appearance in high traffic areas with more frequent cleanings
- Reduce the risk of slip-and-fall when transitioning from damp carpet to hard floors

TENNANTTRUE® PARTS, SERVICE AND FINANCE SOLUTIONS

- Reduce rework, labor and safety costs by using only Tennant True parts and service.
- Ensure optimal cleaning performance by selecting a Tennant True Service program provided by a network of over 400 factorytrained Tennant service representatives.
- Improve uptime by leveraging TennantTrue parts and service.
- Simplify budgeting by bundling TennantTrue service plans, including parts, into the purchase or financing of your machine.



Carpet and Rug Institute (CRI) Seal of Approval – Certified Bronze.

Choose GE Capital or U.S. Bancorp, our leasing providers, for simple, quick financing with flexible upgrade options.

R14 DUAL-TECHNOLOGY CARPET CLEANER

CLEANING SYSTEM

 $\begin{array}{lll} \text{Cleaning path} & 28 \text{ in } / 710 \text{ mm} \\ \text{Productivity (per hour)} & \\ \text{Theoretical max} - \text{ReadySpace}^* & 13,000 \text{ ft}^2 / 1,210 \text{ m}^2 \\ \text{Estimated coverage} - \text{ReadySpace} & 10,000 \text{ ft}^2 / 930 \text{ m}^2 \\ \text{Theoretical max} - \text{Extraction} & 7,500 \text{ ft}^2 / 700 \text{ m}^2 \\ \text{Estimated coverage} - \text{Extraction} & 5,000 \text{ ft}^2 / 470 \text{ m}^2 \\ \end{array}$

BRUSH DRIVE SYSTEM

Brush motor horsepower (2) 0.54 hp / 0.40 kW
Roller/brush RPM 270 rpm / 270 rpm
Roller/brush size (dual cylindrical) 27.5 in / 700 mm
Down pressure
ReadySpace 104 lb / 47 kg standard, 152 lb /

104 lb / 47 kg standard, 152 lb / 69 kg heavy 32 lb / 15 kg standard, 84 lb 38 kg heavy

SOLUTION SYSTEM

Extraction

Solution tank capacity- cleanable Solution pump rated pressure (max) Solution pump pressure ReadySpace Extraction Solution flow rate ReadySpace Extraction

250 psi / 17.2 bar 30 psi / 2.07 bar at spray tips 52 psi / 3.59 bar at spray tips 0.33 gpm / 1.25 lpm

1.24 gpm / 4.7 lpm

32 gal / 121 L

RECOVERY SYSTEM

Recovery tank capacity— cleanable Vacuum fan (2)
Vacuum motor airflow (max)
Vacuum system airflow (actual)
ReadySpace
Extraction
Vacuum motor sealed waterlift
Vacuum system sealed waterlift
Vacuum shoe (2)

28 gal / 106 L 3-stage, 0.6 hp / 0.45 kW 66.5 cfm / 1.88 m³/min 48 cfm / 1.36 m³/min

48 cfm / 1.36 m³/min 32 cfm / 0.91 m³/min 70.5 in / 1,790 mm 56 in / 1,420 mm 16.5 in / 420 mm (removable without tools)

POWER SYSTEM

Standard capacity batteries (24 V) 335 AH
Battery run time (max) 3.0 hr

PROPELLING SYSTEM

Cleaning speed - ReadySpace Standard 100 fpm / 30 mpm Maximum 150 fpm / 46 mpm Cleaning speed – Extraction 50 fpm / 15 mpm 75 fpm / 23 mpm Standard Maximum 290 fpm / 88 mpm Transport speed forward Transport speed reverse 175 fpm / 53 mpm Gradeability 6° / 10.5% 11° / 19.25% Transport at gross weight Transport (empty for trailering) 3° / 5% Working

MACHINE SPECIFICATIONS

 Length
 61.5 in / 1,560 mm

 Width
 31.5 in / 800 mm

 Height
 52 in / 1,320 mm

 Weight
 835 lb / 379 kg

 Weight (with batteries)
 1,225 lb / 556 kg

 Minimum aisle turn
 64 in / 1,630 mm

 Sound level (operator's ear)
 73 dBA

WARRANTY

See your local representative for warranty information

Specifications subject to change without notice.

SEEING IS BELIEVING

For a demonstration or additional information, call +1.800.553.8033 or email info@tennantco.com

Tennant 701 North Lilac Drive Minneapolis, MN 55422 USA

USA/Canada: +1.800.553.8033 Quebec: +1.800.361.9050 Overseas: +1.763.540.1315

www.tennantco.com info@tennantco.com